14th Street Bridge Spanning the lines of the Missouri-Pacific Railroad Company at 14th Street North Little Rock Pulaski County Arkansas HAER No. AR-42

HAER ARK, 60-NOLI, 4-

### **PHOTOGRAPHS**

WRITTEN HISTORICAL AND DESCRIPTIVE DATA

Historic American Engineering Record National Park Service Department of the Interior Washington, DC 20013-7127

### HISTORIC AMERICAN ENGINEERING RECORD

# HAER ARK, 60-NOLI 4-

### 14TH STREET BRIDGE

HAER NO. AR-42

LOCATION:

Spanning the Missouri-Pacific Railroad lines on 14th Street,

in the town of North Little Rock, Arkansas.

UTM: 15/3847275/566840 Quad: North Little Rock

DATE OF CONSTRUCTION:

ca. 1925

MAJOR ALTERATIONS AND ADDITIONS:

The main span of the 14th Street Bridge was removed by the Missouri-Pacific Railroad Company in late May 1988. The reason behind this decision was based on the fact that the bridge did not meet the minimum vertical clearance requirements by one inch. The main span was replaced with a steel stringer span. No large format photography was taken.

PRESENT CONDITION

AND USE:

The approach spans are still in use for vehicular traffic.

STYLE:

Single-span, pony Kingpost timber truss bridge.

BUILDER:

It is assumed that the 14th Street Bridge was designed and

built by the Missouri-Pacific Railroad Company.

ADDITIONAL

INFORMATION:

AHTD Bridge No. 19417, AHPP Resource No. PU2027.

SIGNIFICANCE:

This bridge is the only identified timber Kingpost bridge in

the Arkansas.

HISTORIAN:

Michael Swanda Survey Coordinator

Arkansas Historic Preservation Program

August 26, 1988.

#### STRUCTURAL SYSTEMS

This bridge uses modified Kingpost timber trusses. All timber truss members are square in section. The top chord timbers are attached to the bottom chord with a butt joint and joined at the top of the peak with steel straps. Two timber vertical members are placed in the truss on either side of the center peak and are attached to the top and bottom chords with steel straps (the addition of these verticals modifies the basic kingpost design). A round steel rod center vertical is bolted to a steel plate at the peak of the top chord. This vertical extends through the bottom chord from which a timber floor beam is suspended by a steel plate bolted to the vertical. Timber stringers support a timber planked roadway. The bottom chord rests on a timber beam that is supported by vertical timber piles. Timber pile trestle spans are used on both approaches to the main span. A timber post and plank guardrail runs the entire length of the bridge.

## **DIMENSIONS**

The 14th Street Bridge has a total length of 140 feet. The main span is 32 feet long with a 22 foot wide roadway.

### SOURCES OF INFORMATION

- Bridge Division Files, Arkansas Highway and Transportation Department, Little Rock. Historic Bridge File, Arkansas Historic Preservation Program, Little Rock.
- McClurkan, Burney B. Arkansas' Historic Bridge Inventory, Evaluation Procedures 1987 and Preservation Plan. Manuscript of file, Environmental Division, Arkansas Highway and Transportation Department, Little Rock.